

UNIVERSAL FLUSH ACCESS DOOR

Model DSC-214M

Prime Coated Steel or Stainless Steel

DATE



KARP ASSOCIATES, INC.

260 Spagnoli Road Melville, NY 11747 (631) 768-8300 - Phone (631) 768-8350 - Fax

SPECIFICATIONS

GENERAL SCOPE:

Access doors shall be Karp Type DSC-214M as manufactured by Karp Associates, Inc., Melville, N.Y. Sizes shall be as indicated on the drawings.

CONSTRUCTION:

- 1. Frame shall be 16 gage steel and door shall be 14 gage steel. $\,$
- 2. Flange of frame shall be one-piece construction, 1.00" wide.
- 3. Door and trim shall have radius corners.
- 4. Hinge shall be pin type, spring loaded making door removable.
- 5. Locks shall be flush and screwdriver operated with steel can and studs, or shall be key operated cylinder lock with automatic dust shutter.
- 6. Masonry anchor straps can be included on frames if specified.
- 7. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel. Stainless steel shall have No. 4 satin polish finish.
- * When hinge side is greater than 48", door shall have a continuous piano hinge for rigidity.

STANDARD SIZES

DOOR SIZE H X W (IN.)	WALL/CEILING OPENING (IN.)	# OF LATCHES CRS SS	SHIP WT. (LBS.)
6 x 6	6 3/8 x 6 3/8	1	2.1
8 x 8*	8 3/8 x 8 3/8	1	3.1
10 x 10*	10 3/8 x 10 3/8	1	4.3
12 x 8	12 3/8 x 8 3/8	1	4.6
12 x 12*	12 3/8 x 12 3/8	1	6.3
14 x 14	14 3/8 x 14 3/8	2	8.1
16 x 12	16 3/8 x 12 3/8	2	7.8
16 x 16	16 3/8 x 16 3/8	2	9.9
18 x 12	18 3/8 x 12 3/8	2	8.9
18 x 18*	18 3/8 x 18 3/8	2 4	12.2
20 x 16	20 3/8 x 16 3/8	2	11.8
22 x 22	22 3/8 x 22 3/8	4	16.3
24 x 12	24 3/8 x 12 3/8	2	10.6
24 x 18	24 3/8 x 18 3/8	2	14.5
* STOCK SIZES	AVAILABLE IN S/S		

24 X 18		3/6 × 16 3/6 2 14,	.5		- 1 - 1	
* STOCK SIZE	ES AVAII	LABLE IN S/S				
				OPTIONAL _	Ш	
_				ANCHOR STRAP	$\parallel \parallel \parallel$	
METAL \₁	_	000000000000000000000000000000000000000	TE . 0/0"		ЫI	
STUDDING \		OPENING SIZE = DOOR SIZ	ZE + 3/8" ———	- / ₁	1	
L	_			/		
	_	4 4/40	1101.50	HI	1.	
SHEET	/	1 1/4	HOLES —		Ч	
METAL -	_		$\boldsymbol{\alpha}$			-
SCREW					'	l
CONEW	\Box	10.04.05 1.56"			-	
		16 GAGE 1.56" } }			'	
CALCOVER S	N. 25. 25	FRAME	14 GAGE			
\$240 m			DOOR			
FINISH (1997)			لحيث			
LINE Z	87.2.7.		<u> </u>			
FOR/	1	ı \		\		
DRYWALL		\		FOR MASONRY		
		Domeyahla Hinna		\ TOKWASSINKI		
		└─ Removable Hinge		16 GAGE		
-	- 1"	- ₩		- FLUSH FLANGE		

PROJECT DATA

Project Name:
Architect:

Contractor:

Agent/Customer Name:

Tagging Instructions:

Special Instructions:

To be purchased from Industrial Hardware & Specialties, Inc.

www.industrialhardware.com T:973-684-4010 Fax:973-684-3095




PROJECT SCHEDULE

Qty.	н	w	No. of Latches	Finish	Remarks

DOOR SIZE	WALL/CEILING	# OF	SHIP WT.
H X W (IN.)	OPENING (IN.)	LATCHES	(LBS.)
24 x 20	24 3/8 x 20 3/8	2	16.5
24 x 24*	24 3/8 x 24 3/8	5	18.7
30 x 20	30 3/8 x 20 3/8	5	20.1
30 x 22	30 3/8 x 22 3/8	5	21.7
30 x 24	30 3/8 x 24 3/8	5	23.6
30 x 30	30 3/8 x 30 3/8	5	27.8
36 x 22	36 3/8 x 22 3/8	5	25.6
36 x 24	36 3/8 x 24 3/8	5	28.2
36 x 36	36 3/8 x 36 3/8	5	36.8
48 x 24	48 3/8 x 24 3/8	6	34.4

* The wall opening size for doors larger that 48 x 36 shall be 1/2" larger than the door size.



Made with Union Labor