



## FLUSH CUP PULLS



### 15C

#### Heavy Duty Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls  
Description: Cup welded to face plate  
Face: 3-1/2" x 5" (89 mm x 127 mm)  
Projection: 1/8" (3.2 mm)  
Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)  
Cup Clearance: 3/4" (19 mm)  
Materials: Stainless steel  
Finishes: US32D  
Fasteners: Four (4) #6 x 5/8" OPHWS



### 15N

#### Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls  
Description: Cup welded to face plate  
Face: 3-1/2" x 5" (89 mm x 127 mm)  
Projection: 1/8" (3.2 mm)  
Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)  
Cup Clearance: 3/4" (19 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32D  
Fasteners: Four (4) #6 x 5/8" OPHWS



### 15P

#### Heavy Duty Security Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls  
Description: Cup welded to face plate and welded studs for security torx thru-bolt mounting  
Face: 3-1/2" x 5" (89 mm x 127 mm)  
Projection: 1/8" (3.2 mm)  
Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)  
Cup Clearance: 3/4" (19 mm)  
Materials: Stainless steel  
Finishes: US32D  
Fasteners: Two (2) 6-32 x 1-1/2" FPHMS (Security Torx)  
Notes: For use on 1-3/4" (44 mm) doors



### 15S

#### Light Duty Flush Cup Pull

Certification: Meets ANSI A156.6 for J403 Pulls  
Description: Concealed mounting by screws within the recessed cup (similar to 16N or 17N)  
Face: 3-1/2" x 5" (89 mm x 127 mm)  
Projection: 1/8" (3.2 mm)  
Opening: 1-3/4" x 3-1/16" (44 mm x 78 mm)  
Cup Clearance: 3/4" (19 mm)  
Materials: Aluminum, brass, bronze, stainless steel  
Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32D  
Fasteners: Two (2) #6 x 5/8" PPHWS  
Notes: Fasteners concealed in cup

