



## FLOOR STOPS & HOLDERS



### **245F** **Cast Floor Stop**

Certification: Meets ANSI A156.16 for L02161  
 Base: 1-3/4" x 4" (45 mm x 102 mm )  
 Base Thickness: 1/2" (13 mm)  
 Overall Height: 1-5/16" (33 mm)  
 Materials: Cast brass with grey rubber bumper  
 Finishes: US3, US4, US10, US10B, US26, US26D  
 Fasteners: Two (2) #14 x 1-1/2" FPHWS, two (2) 1/4-20 x 1-1/4" FPHMS, two (2) 1/4-20 lead anchor, and two (2) plastic anchor  
 Notes:
 

- Heavy duty - for use in high traffic areas
- For use with thresholds and undercut doors
- For use on wood or concrete floors



### **246B** **Dome Stop Riser Plate**

Diameter: 1-3/4" (45 mm)  
 Thickness: 3/8" (10 mm)  
 Fasteners: One (1) 1/4-20 x 1" FPHMS  
 Materials: Cast brass  
 Finishes: US3, US4, US10, US10B, US15, US15A, US19, US26, US26D  
 Notes: For use with 241F on undercut doors, doors with thresholds, and carpeted flooring



### **248F** **Modern Style Universal Stop**

Base Diameter: 1-7/16" (37 mm)  
 Height: 1-1/2" (38 mm)  
 Materials: Brass with black rubber bumper  
 Finishes: US26D  
 Fasteners: One (1) #12 x 1-1/4" FPHWS, one (1) plastic anchor, one (1) 1/4-20 x 1" FPHMS, and one (1) 1/4-20 lead anchor



### **248G** **Modern Style Universal Stop**

Base Diameter: 1-7/16" (37 mm)  
 Height: 1-1/2" (38 mm)  
 Materials: Brass with grey rubber bumper  
 Finishes: US26D  
 Fasteners: One (1) #12 x 1-1/4" FPHWS with plastic anchor and one (1) 1/4-20 x 1" FPHMS with lead anchor



### **249F** **L-Shaped Floor Stop**

Base: 1" x 2-1/2" x 7/32" thick (25 mm x 64 mm x 6 mm)  
 Base Thickness: 1/4" (6 mm)  
 Overall Height: 2-5/8" (67 mm)  
 Stop face: Resilient black rubber  
 Materials: Steel  
 Fasteners: Two (2) #14 x 1-1/2" FPHWS and two (2) plastic anchors  
 Notes: 1-1/2" (38 mm) max door to floor clearance

