



FLOOR STOPS & HOLDERS



252F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-1/2" (40 mm x 64 mm)

Overall Height:

2-11/16" (68 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchor, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors
- 2" (51 mm) max door to floor clearance



257F

Floor Stop

Certification:

Meets ANSI A156.16 for L02131

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Overall Height:

2" (51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US15A, US19, US26, US26D

Fasteners:

One (1) #14 x 1-1/2" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, one (1) plastic anchor, one (1) 5/16-18 x 2-1/2" threaded stud, and one (1) 5/16-18 x 2-1/2" combo threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on wood or concrete floors



258F

Floor Stop and Holder

Certification:

Meets ANSI A156.16 for L01371

Base:

1-9/16" x 2-15/32" (40 mm x 63 mm)

Height:

3" (76 mm)

Keeper:

1" x 2" (25 mm x 51 mm)

Materials:

Cast brass with black rubber bumper

Finishes:

US3, US10, US10B, US15, US26, US26D

Fasteners:

Two (2) #10 x 1" FPHWS, one (1) 1/4-20 x 3/4" FPHMS, one (1) 5/16-18 lead anchor, one (1) 1/4-20 lead anchors, and one (1) 5/16-18 x 2-1/2" threaded stud

Notes:

- 1-3/8" (35 mm) max door to floor clearance
- Heavy duty - for use in high traffic areas
- For use on concrete floors
- Manual holder ideal for interior and exterior applications
- Unit functions as a stop, but can serve as a "Hold Open" when hook is manually engaged