




FLUSH BOLTS & COORDINATING DEVICES



283D

Manual Flush Bolt

- Certification: Meets ANSI A156.16 for L14261
 Face Plate: 1" x 6-25/32" (25 mm x 172 mm)
 Bolt Head: 1/2" (13 mm) square
 Bolt Throw: 3/4" (19 mm)
 Bolt Backset: 3/4" (19 mm)
 Mortise Strike: 15/16" x 2-1/4" (24 mm x 57 mm)
 Materials: Brass faceplate with steel components
 Finishes: US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D
 Fasteners: Eight (8) #8 x 3/4" combo screws
 Notes:
 - For use on wood composite/ fire-rated doors
 - Non-handed
 - Bolt head rods are adjustable
 - 1-1/2 hour fire rating for wood doors up to 4 feet wide by 10 feet tall



291D

Automatic Flush Bolt Set for Wood Covered Composite Doors

- Certification: B, C, D, and E Label
 ANSI A156.3 Type #25
 Face Plate: 1" x 8-1/2" (25 mm x 216 mm)
 Bolt Head: 1/2" (13 mm) square
 Bolt Throw: 3/4" (19 mm)
 Bolt Backset: 3/4" (19 mm)
 Mortise Strike: 15/16" x 2-1/4" (24 mm x 57 mm)
 Materials: Stainless steel and brass with steel components
 Finishes: US3, US4, US10, US10B, US15, US32, US32D
 Fasteners: Six (6) #8 x 1" combo screws, three (3) #10 x 1" SMS, and two (2) plastic anchors
 Notes:
 - Thermal lock automatically locks inactive door under high fire/heat conditions
 - 280X dust proof strikes are recommended for use with these sets
 - Used in pairs at top and bottom of inactive door
 - Fully automatic – bolts retract when active door is opened; bolts extend when active door is closed
 - Non-handed
 - Bolt head rods are adjustable
 - 1-1/2 hour fire rating for wood doors up to 4 feet wide by 9 feet tall