

1E

6

152

2E

6

152

3E

6

152

2G

8

203

2J

10

254

3J

10

254

3G

8

203

3L

12

305

1G

8

203

1J

10

254

CTC Length

Millimeters

CTC Length

Millimeters

CTC Length

Millimeters

Inches

Inches

Inches



1L

12

305

2L

12

305

PULLS

1

Modified Half Round Wrought Door Pull

Certification: Meets ANSI A156.6 for J401 Pulls Base: 1/2" x 1" (13 mm x 25 mm)

Projection: 2" (51 mm) Clearance: 1-1/2" (38 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Aluminum, brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D

Fasteners: Two (2) 1/4-20 x 2-1/4" FPHMS with finish washers
Handicap: • 2-1/2" (64 mm) clearance available on special orders

Add prefix "H" to number (i.e., H1E)

Options: • May be combined with a plate to make a pull plate

• Other centers on special order

Notes:

• For sizes or finishes not listed in this catalog, contact Hager Customer Service

for availability

Not suitable for back to back mounting

2

Rectangular Wrought Door Pull

Certification: Meets ANSI A156.6 for J401 Pulls Base: 3/8" x 1-1/4" (10 mm x 32 mm)

Projection: 2" (51 mm) Clearance: 1-5/8" (41 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Aluminum, brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D

Fasteners: Two (2) 1/4-20 x 2-1/4" FPHMS with finish washers Handicap: • 2-1/2" (64 mm) clearance available on special orders

• Add prefix "H" to number (i.e., H2E)

Options: • May be combined with a plate to make a pull plate

Other centers on special order

Notes: • For sizes or finishes not listed in this catalog, contact Hager Customer Service

for availability

• Not suitable for back to back mounting



3

Round Wrought Door Pull

Certification: Meets ANSI A156.6 for J401 Pulls

Base Diameter: 3/4" (19 mm)

Projection: 2-1/4" (57 mm)

Clearance: 1-1/2" (38 mm)

Door Thickness: 1-3/4" (45 mm) - Standard

Materials: Aluminum, brass, bronze, stainless steel

Finishes: US3, US4, US10, US10B, US26, US26D, US28, US32, US32D

Fasteners: Two (2) 1/4-20 x 2-1/4" FPHMS with finish washers
Handicap: • 2-1/2" (64 mm) clearance available on special orders

• Add prefix "H" to number (i.e., H3E)

Notes:

• For sizes or finishes not listed in this catalog, contact Hager Customer Service

for availability

• May be combined with a plate to make a pull plate

• Other centers on special order

• If ordered with tempered glass, specify glass thickness and hole size

Back to back - see model 13

