

790-909

Swing Clear - Door of Any Material



Material:

- 14 Ga. (0.075" = 1.9 mm) Type 304 Stainless Steel

Finish:

- US32D Satin

PRODUCT SPECIFICATIONS

CLEARANCE:

- 1/8" (.08 mm) minimum recommended hinge side
- Plus standard lockside clearance

FASTENERS:

- #10-24 x 5/8" S/S Drill-Kwik (R) (metal frame)
- #1/4-20 x 3/4" 2C Drill-Kwik (R) (metal door)
- #1/4-14 x 1" 2C Type AB (wood frame)

LENGTH OPTIONS:

- Standard

DOOR REINFORCEMENT:

- None required to 200 lbs. Heavier weight use 16-gauge channel.

FRAME REINFORCEMENT:

- None required to 200 lbs. Heavier weight use 16-gauge channel.

FIRE RATING:

- Up to 3 hr. metal and 90 min. wood composite

SPECIAL FEATURES:

- 1/4" (6.3 mm) diameter Stainless Steel Pin
- Dual 6/6 Nylon bearings between each knuckle
- Useful for ADA upgrade work
- Security molding
- For beveled or square edge doors
- 1/8" (3.2 mm) inset

NOTE:

-Any nonstandard length hinge may require a custom hole pattern based on the requested length. Consult Hager Companies to address the field prep for the doors and frames.

PRODUCT SIZE OPTIONS

LENGTH (INCHES)	LENGTH (CM)	SCREWS (DOOR)	SCREWS (JAMB)
79	200.7	13	19
83	210.8	14	21
85	215.9	14	21
95	241.3	15	23
119	302.3	18	27