

790-915

Door of Any Material

Certification:

- ANSI A51011B Grade 1 for 150-pound doors

Material:

- 14 Ga. (0.075" = 1.9 mm) Type 304 Stainless Steel

Finish:

- US32D Satin



PRODUCT SPECIFICATIONS

CLEARANCE:

- 7/32" (5.6 mm) hinge side

FASTENERS:

- #10-24 x 5/8" S/S Dril-Kwik (R) (metal frame)
- #10-16 x 1-1/4" S/S Type AB (wood door)

LENGTH OPTIONS:

- Standard and Custom

DOOR/FRAME REINFORCEMENT:

- None required to 200 lbs. Heavier weight use 16-gauge channel.

FIRE RATING:

- Up to 3 hr. metal and 90 min. wood composite

ELECTRIC

MODIFICATIONS:

- Power Transfer Preparation (EPT 2) or (EPT 10)
- Exposed Electric Switches (E1S)
- Electric Through-Wire (ETW)

SPECIAL FEATURES:

- 1/4" (6.3 mm) diameter Stainless Steel Pin
- Dual 6/6 Nylon bearings between each knuckle
- Door edge protection lip (stop side only)
- Not recommended for doors with a beveled edge on the hinge side
- 1/16" (1.6 mm) inset

NOTE:

- Any nonstandard length hinge may require a custom hole pattern based on the requested length. Consult Hager Companies to address the field prep for the doors and frames.
- Tamper resistant hospital tip available