


ADVANCED CABLE TIES PART NUMBER	PANEL THICKNESS		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	ANSI/UL 94 MH FLAMABILITY RATING		
	IN (mm)										
AP(R, L)-PMW-9-C	.244 (6.200mm)		.394 (10.000mm)	.098 (2.500mm)	.319 (8.100mm) +/- .010 (.250mm)	.230 (7.800mm)	.295 (7.500mm)	.126 (3.200mm)	V-2		
AP(R, L)-PMW1-9-C	.047-.109 (1.19-2.77mm)		.280 (7.100mm)	.065 (1.600mm)	.250 (6.300mm) +/- .010 (.250mm)	.260 (6.800mm)	.240 (6.136mm)	.138 (3.504mm)	V-2		
AP(R, L)-PMW1-0-C	.047-.109 (1.19-2.77mm)		.280 (7.100mm)	.065 (1.600mm)	.250 (6.300mm) +/- .010 (.250mm)	.260 (6.800mm)	.240 (6.136mm)	.138 (3.504mm)	V-2		
											
						ADVANCED CABLE TIES – WING STYLE PUSH MOUNTS					
						COLOR DESIGNATIONS:			MATERIAL:		
						9 = NATURAL 0 = BLACK			NYLON 6/6 POLYAMIDE		
						B	4/27/17	JA	KT	KT	NEW LOGO ADDED.
A	2/29/16	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE		
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/27/17	KT	NONE		

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.78.1