

COLOR CABLE TIES



INDOOR COLOR CODES

1 = Brown	8 = Gray
2 = Red	11 = Fluorescent Green
3 = Orange	12 = Fluorescent Pink
4 = Yellow	13 = Fluorescent Yellow
5 = Green	14 = Fluorescent Orange
6 = Blue	15 = Fluorescent Blue
7 = Purple	18 = Pink



OUTDOOR WEATHERABLE UV COLOR CODES

1UV = Brown	8UV = Gray
2UV = Red	11UV = Fluorescent Green
3UV = Orange	12UV = Fluorescent Pink
4UV = Yellow	13UV = Fluorescent Yellow
5UV = Green	14UV = Fluorescent Orange
6UV = Blue	15UV = Fluorescent Blue
7UV = Purple	18UV = Pink



- High quality color concentrates and manufacturing processes produce color consistency time after time.
- Custom colors are available.
- Ideal Applications: Color Coding, Packaging Continuity, Identification, Bundling Aesthetics, etc.



Color Cable Ties									
Per Bag	ACT Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Mil-Spec	Per Case
100	AL-04-18-#-C	Ref. Chart	4.12/104.77	.095/2.413	.042/1.066	18 lb./80 n.	.875/22.2	MS3367-4*	10,000
100	AL-05-40-#-C	Ref. Chart	5.84/148.33	.140/3.556	.049/1.244	40 lb./178 n.	1.437/36.4	MS3367-5*	5,000
100	AL-08-40-#-C	Ref. Chart	8.875/225.42	.140/3.556	.049/1.244	40 lb./178 n.	2.375/60.3		5,000
100	AL-07-50-#-C	Ref. Chart	7.56/192.07	.180/4.572	.052/1.320	50 lb./222 n.	1.875/47.6	MS3367-1*	5,000
100	AL-11-50-#-C	Ref. Chart	11.25/285.75	.180/4.572	.052/1.320	50 lb./222 n.	3.062/77.7	MS3367-7*	5,000
100	AL-14-50-#-C	Ref. Chart	14.25/361.95	.180/4.572	.052/1.320	50 lb./222 n.	4.00/101.6	MS3367-2*	5,000
100	AL-14-120-#-C	Ref. Chart	15.09/383.36	.300/7.620	.076/1.930	120 lb./534 n.	4.06/103.1	MS3367-3*	2,000

Tolerance: .xxx = +/- .005, .xx = +/- .015, 14" 120 lb. is not available in brown and fluorescent yellow, Sold in case quantities

*Mil-Spec does not apply to fluorescent colors.

UV Color Cable Ties									
Per Bag	ACT Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Mil-Spec	Per Case
100	AL-04-18-#UV-C	Ref. Chart	4.12/104.77	.095/2.413	.042/1.066	18 lb./80 n.	.875/22.2		10,000
100	AL-05-40-#UV-C	Ref. Chart	5.84/148.33	.140/3.556	.049/1.244	40 lb./178 n.	1.437/36.4		5,000
100	AL-08-40-#UV-C	Ref. Chart	8.875/225.42	.140/3.556	.049/1.244	40 lb./178 n.	2.375/60.3		5,000
100	AL-07-50-#UV-C	Ref. Chart	7.56/192.07	.180/4.572	.052/1.320	50 lb./222 n.	1.875/47.6		5,000
100	AL-11-50-#UV-C	Ref. Chart	11.25/285.75	.180/4.572	.052/1.320	50 lb./222 n.	3.062/77.7		5,000
100	AL-14-50-#UV-C	Ref. Chart	14.25/361.95	.180/4.572	.052/1.320	50 lb./222 n.	4.00/101.6		5,000
100	AL-14-120-#UV-C	Ref. Chart	15.09/383.36	.300/7.620	.076/1.930	120 lb./534 n.	4.06/103.1		2,000

Tolerance: .xxx = +/- .005, .xx = +/- .015, 14" 120 lb. is not available in brown and fluorescent yellow, Sold in case quantities; Minimum purchase required

*Mil-Spec does not apply to UV colors.

Additional Product Lines



Type 21S
AH-2
Supporting
Device



Type 21
AH-2
Positioning
Device

Advanced Cable Ties, Inc.
 245 Suffolk Lane, Gardner, MA 01440
 800-861-7228 - sales@actfs.com - www.advancedcableties.com