


## Cam-Alloy Chain Slings Single Types: S and C




Type C0




Type SOS




Type SOG




Type SSG



Type SSS



Type SOF







Type SOSL

Chain Size		System	Oblong Link							Working Load Limit	
			Nominal Size Material		Inside Dimensions						
			in.	mm	Width		Length				
9/32	7	10	37/64	15	2 1/2	64	5	127	4,300	1,950	
3/8	10	10	13/16	21	3	76	6	152	8,800	4,000	
1/2	13	10	1 1/8	29	4	102	8	203	15,000	6,800	
5/8	16	10	1 1/8	29	4	102	8	203	22,600	10,300	
3/4	20	10	1 1/4	32	4	102	8	203	35,300	16,000	
7/8	22	10	1 5/8	41	5 1/4	133	10 1/2	267	42,700	19,400	
1	26	8	1 7/8	48	6	152	12	305	47,700	21,600	
1 1/4	32	8	2	51	7	178	14	356	72,300	32,800	

Dimensions are approximate. Single chain slings are available in other combinations. These items are made to order.

## Cam-Alloy Chain Slings Double Type: D



Chain Size		System	Oblong Master Link						Working Load Limit					
			Nominal Size Material		Inside Dimensions				60°		45°		30°	
			in.	mm	Width		Length		Double at 60°		Double at 45°		Double at 30°	
9/32	7	10	37/64	15	2 1/2	64	5	127	7,400	3,400	6,100	2,700	4,300	1,950
3/8	10	10	13/16	21	3	76	6	152	15,200	6,900	12,400	6,900	8,800	3,990
1/2	13	10	1 1/8	29	4	102	8	203	26,000	11,800	21,200	9,600	15,000	6,800
5/8	16	10	1 1/4	32	4	102	8	203	39,100	17,700	32,000	14,500	22,600	10,300
3/4	20	10	1 5/8	41	5 1/4	133	10 1/2	267	61,100	27,700	49,900	22,600	35,300	16,000
7/8	22	10	1 7/8	48	6	152	12	305	74,000	33,500	60,400	27,350	42,700	19,400
1	26	8	2	51	7	178	14	356	82,600	37,900	67,400	31,000	47,700	21,600
1 1/4	32	8	2 1/4	57	8	203	16	406	125,200	56,800	102,200	46,400	72,300	32,800

Dimensions are approximate. Double chain slings are available in other combinations. These items are made to order.

SLINGS