


PlastiSert Press-Fit Flush Bottom Slot

ZONE		REV.	REVISIONS	DATE	APPROVED
			DESCRIPTION		

INSPEC


Diameter Thread Pitch

10-32



0.375

0.250



0.262

Suggested Drill Bit Size



0.2500 (1/4)

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

			NAME	DATE
			DRAWN	
			CHECKED	
			ENG APPR.	
			MFG APPR.	
			Q.A.	
			COMMENTS:	
NEXT ASSY	USED ON			
APPLICATION	DO NOT SCALE DRAWING			

TH. STANDARD: ANSI/ASME
ACRONYM: UNF
ROTATION: Right-Hand
MATERIAL FINISH
Stainless Steel Type 303

PART NUMBER
35L5C-KVRW-10-05



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE:1:8	WEIGHT:	SHEET 1 OF 1