




WireSert Free-Running

Diameter Thread Pitch

12-24

Tang



0.432

Suggested Drill Bit Size 0.2344 (15/64)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	8118-368-00-0435	NAME	DATE
TH. STANDARD:	ANSI/ASME	DRAWN	
ACRONYM:	UNC	CHECKED	
ROTATION:	Right-Hand	ENG APPR.	
MATERIAL FINISH	Stainless Steel 18-8	MFG APPR.	
PART NUMBER	35L7C-C82Y-01220-34	Q.A.	
NEXT ASSY	USED ON	COMMENTS:	
APPLICATION	DO NOT SCALE DRAWING		



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE: 1:8	WEIGHT: 0.04	SHEET 1 OF 1