

WireSert Free-Running

Diameter Thread Pitch

1/2-20

Tang



0.75

Suggested Drill Bit Size 0.5156 (33/64)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	5340-00-291-3488	NAME	DATE
MILITARY STANDARD	MS124700	DRAWN	
		CHECKED	
		ENG APPR.	
TH. STANDARD: ANSI/ASME		MFG APPR.	
ACRONYM: UNF		Q.A.	
ROTATION: Right-Hand		COMMENTS:	
MATERIAL FINISH	Stainless Steel 18-8		
PART NUMBER	35L7C-C83G-05015-1J		
NEXT ASSY	USED ON		
APPLICATION	DO NOT SCALE DRAWING		



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE: 1:8	WEIGHT: 0.45	SHEET 1 OF 1