

WireSert Free-Running

Diameter Thread Pitch

3/4-16

Tang



1.5

Suggested Drill Bit Size 0.7656 (49/64)



| ZONE | | REV. | REVISIONS DESCRIPTION | DATE | APPROVED |
|------|--|------|-----------------------|------|----------|
| | | | | | |

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

| | | |
|---|----------------------|-----------|
| NATIONAL STOCK NUMBER 5340-00-200-7222 | NAME | DATE |
| MILITARY STANDARD MS124743 | DRAWN | |
| TH. STANDARD: ANSI/ASME ACRONYM: UNF | CHECKED | |
| ROTATION: Right-Hand | ENG APPR. | |
| MATERIAL FINISH Stainless Steel 18-8 | MFG APPR. | |
| PART NUMBER 35L7C-C83G-07520-0F | Q.A. | |
| NEXT ASSY | USED ON | COMMENTS: |
| APPLICATION | DO NOT SCALE DRAWING | |



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

| | | |
|------------------|--------------|--------------|
| SIZE A | DWG. NO. | REV. |
| SCALE: 1:8 | WEIGHT: 0.53 | SHEET 1 OF 1 |