



WireSert Free-Running

Diameter Thread Pitch

M12 x 1.25

Tang



Suggested Drill Bit Size  0.4844 (31/64)

REV. NO.		REVISIONS	DATE	APPROVED
ZONE	REV.	DESCRIPTION		

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES, INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES, INC. IS STRICTLY PROHIBITED.

				NAME	DATE
				DRAWN	
				CHECKED	
				ENG APPR.	
				MFG APPR.	
				Q.A.	
				COMMENTS:	
NEXT ASSY	USED ON	TH. STANDARD: ISO Metric ACRONYM: Spark Plug (ISO) ROTATION: Right-Hand MATERIAL FINISH Stainless Steel 18-8	PART NUMBER 35L7C-C84R-C12H16-06		
APPLICATION		DO NOT SCALE DRAWING			



**INDUSTRIAL
HARDWARE**
AND SPECIALTIES INCORPORATED

**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE: 1:8	WEIGHT: 0.06	SHEET 1 OF 1