

WireSert Locking

Diameter Thread Pitch

2-56

Tang



0.129

Suggested Drill Bit Size

0.0938 (3/32)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	5340-00-215-0248	NAME	DATE
MILITARY STANDARD	MS21209-C0215	DRAWN	
TH. STANDARD: ANSI/ASME		CHECKED	
ACRONYM: UNC		ENG APPR.	
ROTATION: Right-Hand		MFG APPR.	
MATERIAL FINISH		Q.A.	
Stainless Steel 18-8		COMMENTS:	
PART NUMBER	35L7C-C8JJ-00215-34		
NEXT ASSY	USED ON		
APPLICATION	DO NOT SCALE DRAWING		



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE: 1:8	WEIGHT: 0.02	SHEET 1 OF 1