



WireSert Locking

Diameter Thread Pitch

3-48

Tang



Suggested Drill Bit Size 0.1065 (#36)



0.148

ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

MILITARY STANDARD MS21209-C0315	DRAWN	NAME	DATE
TH. STANDARD: ANSI/ASME ACRONYM: UNC ROTATION: Right-Hand MATERIAL FINISH Stainless Steel 18-8	CHECKED		
PART NUMBER 35L7C-C8JJ-00315-34	ENG APPR.		
NEXT ASSY	MFG APPR.		
USED ON	Q.A.		
APPLICATION	COMMENTS:		
	DO NOT SCALE DRAWING		



**INDUSTRIAL
HARDWARE**
AND SPECIALTIES INCORPORATED

**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		

SCALE: 1:8 WEIGHT: 0.01 SHEET 1 OF 1