


# WireSert Locking

Diameter Thread Pitch

6-32

Tang



0.345

Suggested Drill Bit Size

0.1495 (#25)



ZONE		REV.	REVISIONS DESCRIPTION	DATE	APPROVED

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

NATIONAL STOCK NUMBER	5340-00-213-8727	NAME	DATE
MILITARY STANDARD	MS21209-C0625	DRAWN	
TH. STANDARD: ANSI/ASME		CHECKED	
ACRONYM: UNC		ENG APPR.	
ROTATION: Right-Hand		MFG APPR.	
MATERIAL FINISH		Q.A.	
Stainless Steel 18-8		COMMENTS:	
PART NUMBER	35L7C-C8JJ-00625-34		
NEXT ASSY	USED ON		
APPLICATION	DO NOT SCALE DRAWING		



**17-B KENTUCKY AVENUE  
PATERSON, NEW JERSEY 07503  
TEL: 973-684-4010 FAX: 973-684-3095  
email: TechSupport@industrialhardware.com  
www.industrialhardware.com**

SIZE	DWG. NO.	REV.
<b>A</b>		
SCALE: 1:8	WEIGHT: 0.08	SHEET 1 OF 1