

WireSert Locking

Diameter Thread Pitch

5/8-18

Tang



0.938

Suggested Drill Bit Size 0.6406 (41/64)



| ZONE | | REV. | REVISIONS DESCRIPTION | DATE | APPROVED |
|------|--|------|-----------------------|------|----------|
| | | | | | |

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES, INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES, INC. IS STRICTLY PROHIBITED.

| | | | |
|-------------------------|----------------------|-----------|------|
| NATIONAL STOCK NUMBER | 5340-00-834-8362 | NAME | DATE |
| MILITARY STANDARD | MS21209-F1015 | DRAWN | |
| TH. STANDARD: ANSI/ASME | | CHECKED | |
| ACRONYM: UNF | | ENG APPR. | |
| ROTATION: Right-Hand | | MFG APPR. | |
| MATERIAL FINISH | Stainless Steel 18-8 | Q.A. | |
| PART NUMBER | 35L7C-C8K4-06215-1J | COMMENTS: | |
| NEXT ASSY | USED ON | | |
| APPLICATION | DO NOT SCALE DRAWING | | |



**17-B KENTUCKY AVENUE
PATERSON, NEW JERSEY 07503
TEL: 973-684-4010 FAX: 973-684-3095
email: TechSupport@industrialhardware.com
www.industrialhardware.com**

| | | |
|------------|--------------|--------------|
| SIZE | DWG. NO. | REV. |
| A | | |
| SCALE: 1:8 | WEIGHT: 0.79 | SHEET 1 OF 1 |