




WireSert Locking

Diameter Thread Pitch

M11 x 1.25

Tang



16.5mm

Suggested Drill Bit Size

0.4531 (29/64)



ZONE		REV.	REVISIONS		DATE	APPROVED
			DESCRIPTION			

PROPRIETARY AND CONFIDENTIAL
 THIS DRAWING AND IT'S CONTENT IS THE SOLE PROPERTY OF INDUSTRIAL HARDWARE & SPECIALTIES,INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDUSTRIAL HARDWARE & SPECIALTIES,INC. IS STRICTLY PROHIBITED.

				NAME	DATE
				DRAWN	
				CHECKED	
				ENG APPR.	
				MFG APPR.	
				Q.A.	
				COMMENTS:	
NEXT ASSY	USED ON	TH. STANDARD: ISO Metric ACRONYM: ISO ROTATION: Right-Hand MATERIAL FINISH Stainless Steel 18-8	PART NUMBER 35L7C-C8M2-C11H15-1J		
APPLICATION	DO NOT SCALE DRAWING				



**17-B KENTUCKY AVENUE
 PATERSON, NEW JERSEY 07503
 TEL: 973-684-4010 FAX: 973-684-3095
 email: TechSupport@industrialhardware.com
 www.industrialhardware.com**

SIZE	DWG. NO.	REV.
A		
SCALE:1:8	WEIGHT: 0.416	SHEET 1 OF 1