

# Fire-Rated Security

## ACCESS DOOR

The insulated Fire-Rated Security Access Door is constructed of heavy-duty materials to prevent unwanted access through openings in fire-rated walls.

### FEATURES

**FIRE-RATED** Independent third-party tested and UL listed and labeled for 1-1/2 hour fire rating.

**SELF-CLOSING** This door is designed with a spring for secure self-closing wall applications.

**CUSTOM SIZES** Custom sizes are available from 6 inches by 6 inches to 24 inches by 72 inches or 48 inches by 48 inches.



### DETAILS

#### DOOR

- Outer Door: 14 gage Steel
- Inner Door: 20 gage Steel

**FRAME** 16 gage Steel

#### SIZE

- Min: 6 inches by 6 inches
- BST Max: 24 inches by 72 inches or 48 inches by 48 inches
- BSW/BSP Max: 36 inches by 48 inches

**INSTALLATION** Wall

**FLANGE** Exposed, Drywall Bead or Plaster Bead

#### HINGE

- BST: Flush Continuous Piano
- BSW/BSP: Concealed Pin

**FINISH** White Powder Coat

**INSULATION** 2 inch thick Fire-Rated Mineral Wool


**CERTIFICATION** UL listed "B" label for 1-1/2 hours

### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BS</b>				<b>X</b>		
	<b>T</b> 1 inch Flange <b>W</b> Drywall Bead <b>P</b> Plaster Bead	<b>D</b> Detention Lock Prep <b>K</b> Knurled Latch/Key Operated Latch Bolt <b>M</b> Mortise Lock (1-1/8") Prep	<b>Standard Sizes (W x L)</b> 12" x 12"    22" x 30"    24" x 40" 16" x 16"    24" x 24"    24" x 48" 18" x 18"    24" x 36"			<b>B</b> Galvannealed <b>G</b> Gasketing <b>M</b> Masonry Anchors <b>S</b> Type 304 Stainless Steel

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.

### MATERIALS




White Powder Coat


### FLANGES



1 inch Flange



Drywall Bead




Plaster Bead

### LATCHES



Knurled Knob



Mortise Lock Prep