

# Lightweight

## ACCESS DOOR

Babcock-Davis' non-rated insulated Lightweight Access Door offers a solution to larger openings in ceiling applications. The door is available in pre-finished, embossed, galvanized steel and aluminum door skins.

### DETAILS

**DOOR** 26 gage Steel, Embossed

**FRAME** .045 inch 6063-T5 Extruded Aluminum

### SIZE

- Min: 12 inches by 12 inches
- Max: 18 inches by 72 inches, 24 inches by 60 inches or 48 inches by 48 inches

**INSTALLATION** Ceiling or Wall

**FLANGE** Rolled 1-5/16 inches Wide

**HINGE** Aluminum Continuous Piano

### FINISH

- Door Skin: Steel, White Embossed
- Frame: Aluminum, Clear Anodized

**INSULATION** 3/4 inch Polystyrene, R-3.8



### ORDER GUIDE

| BASE       | LATCH                          | WIDTH                  | X         | LENGTH    | OPTIONS                        |
|------------|--------------------------------|------------------------|-----------|-----------|--------------------------------|
| <b>BLW</b> |                                |                        | <b>X</b>  |           |                                |
|            | <b>L</b> Key Operated Cam Lock | Standard Sizes (W x L) |           |           | <b>A</b> Aluminum Panel Insert |
|            | <b>T</b> Screwdriver Cam Latch | 12" x 12"              | 24" x 24" | 30" x 36" | <b>G</b> Gasketing             |
|            |                                | 18" x 18"              | 24" x 36" | 48" x 48" |                                |
|            |                                | 22" x 30"              | 24" x 48" | 60" x 48" |                                |
|            |                                | 22" x 36"              | 30" x 30" | 72" x 48" |                                |

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.  
\*Double door construction.

# Plastic

## ACCESS DOOR

The Plastic Access Door provides an economical alternative to traditional materials and is ideal for light-duty applications. The removable panel is easily installed - no fasteners required.

### DETAILS

**DOOR** 1/8 inch High Impact Styrene, Removable

**FRAME** Reversible 3/4 inch Flange

### SIZE

- Min: 4 inches by 6 inches
- Max: 22 inches by 22 inches

**INSTALLATION** Ceiling or Wall

**FLANGE** Exposed

**LATCH** Snap Latch

**FINISH** White, Texturized



### ORDER GUIDE

| BASE       | WIDTH                  | X         | LENGTH |
|------------|------------------------|-----------|--------|
| <b>BPL</b> |                        | <b>X</b>  |        |
|            | Standard Sizes (W x L) |           |        |
|            | 4" x 6"                | 12" x 12" |        |
|            | 6" x 9"                | 14" x 14" |        |
|            | 8" x 8"                | 22" x 22" |        |