# Uninsulated

# FIRE-RATED ACCESS DOOR

Babcock-Davis' UL Listed Uninsulated Access Door is designed for use in fire-rated walls while providing access to critical building components.

#### DETAILS

**DOOR** 14 gage Steel, Self-Closing

FRAME 16 gage Steel

#### SIZE

- Min: 6 inches by 6 inches
- BUT Max: 24 inches by 72 inches or 48 inches by 48 inches
- BUW/BUP Max: 36 inches by 48 inches

#### **INSTALLATION** Wall

FLANGE Exposed, Drywall Bead or Plaster Bead

#### HINGE

- BUT: Flush Continuous Piano
- BUW/BUP: Concealed Pin

**FINISH** White Powder Coat

**CERTIFICATION** UL listed "B" label for 1-1/2 hours



### **ORDER GUIDE**

BASE	FLANGE	LATCH	WIDTH	X L	.ENGTH	OPTIONS
BU				x		
	T 1 inch flange	K Knurled latch/	Standard Sizes (W x L)			<b>B</b> Galvannealed
	<b>W</b> Drywall bead	key operated latch bolt		24" x 30" 24" x 36"	<b>G</b> Gasketing	
	P Plaster Bead	M Mortise lock	12" x 12"	20" x 30"	24" x 48"	M Masonry Anchors
		(1-1/8") prep	12" x 24" 14" x 14"	22" x 22" 22" x 30" 22" x 36" 24" x 24"	30" x 30" 32" x 32" 36" x 36" 36" x 48"	<b>S</b> Type 304 Stainless Steel

Rough opening is door size +1/4 inch minimum. Additional sizes available, call for more information.

# **Oversized Attic**

## FIRE-RATED ACCESS DOOR

The Oversized Attic Access Door allows access into ceilings when over-sized or double door applications are required. The double leaf design, with a removable center mullion, allows objects to clear which may interfere with door openings.

## **DETAILS**

DOOR 18 gage Steel

FRAME 16 gage Steel

#### SIZE

- Min: 36 inches by 60 inches
- Max: 48 inches by 60 inches

INSTALLATION Wall or Ceiling

**FLANGE** Exposed

**HINGE** Continuous Rod or Piano

FINISH Off White Prime Coat

**CERTIFICATION** Warnock-Hersey listed for 2 hours





### **ORDER GUIDE**

BASE	WIDTH	Χ	LENGTH	0	PTIONS		
BFRD		х					
	Standard Sizes (W x L)			С	C Ceiling Application		
	36" x 60" 40	36" x 60" 40" x 60" 48" x 60"		D	Double Door		
				М	Mortise Lock (1-1/8") prep		
				s	Type 304 Stainless Steel		
				Т	3-Hour Rated		
				W	Wall Application		

Rough opening is door size. Additional sizes available, call for more information.