

Lightweight

ACCESS DOOR

Babcock-Davis' non-rated insulated Lightweight Access Door offers a solution to larger openings in ceiling applications. The door is available in pre-finished, embossed, galvanized steel and aluminum door skins.

DETAILS

DOOR 26 gage Steel, Embossed

FRAME .045 inch 6063-T5 Extruded Aluminum

SIZE

- Min: 12 inches by 12 inches
- Max: 18 inches by 72 inches, 24 inches by 60 inches or 48 inches by 48 inches

INSTALLATION Ceiling or Wall

FLANGE Rolled 1-5/16 inches Wide

HINGE Aluminum Continuous Piano

FINISH

- Door Skin: Steel, White Embossed
- Frame: Aluminum, Clear Anodized

INSULATION 3/4 inch Polystyrene, R-3.8



ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
BLW			X		
	L Key Operated Cam Lock	Standard Sizes (W x L)			A Aluminum Panel Insert
	T Screwdriver Cam Latch	12" x 12"	24" x 24"	30" x 36"	G Gasketing
		18" x 18"	24" x 36"	48" x 48"	
		22" x 30"	24" x 48"	60" x 48"	
		22" x 36"	30" x 30"	72" x 48"	

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.
*Double door construction.

Plastic

ACCESS DOOR

The Plastic Access Door provides an economical alternative to traditional materials and is ideal for light-duty applications. The removable panel is easily installed - no fasteners required.

DETAILS

DOOR 1/8 inch High Impact Styrene, Removable

FRAME Reversible 3/4 inch Flange

SIZE

- Min: 4 inches by 6 inches
- Max: 22 inches by 22 inches

INSTALLATION Ceiling or Wall

FLANGE Exposed

LATCH Snap Latch

FINISH White, Texturized



ORDER GUIDE

BASE	WIDTH	X	LENGTH
BPL		X	
	Standard Sizes (W x L)		
	4" x 6"	12" x 12"	
	6" x 9"	14" x 14"	
	8" x 8"	22" x 22"	