

AB850


Three Knuckle
Concealed Anti-Friction Bearing
Heavy Weight

Application:

- ANSI A2111 (Brass)
- ANSI A5111 (Stainless Steel)
- Non-rising removable pin with flush pin and plug.
- For use on heavy weight doors or doors requiring high frequency service

Electric Modifications:

- [EMN](#) (Electric Monitor Only)
- [ETW](#) (Electric Through-Wire Only)
- [ETM](#) (Electric Through-Wire with Monitoring)
- [Quick Connect](#)



PRODUCT SPECIFICATIONS

MATERIAL:

- Brass with Stainless Steel pin
- Stainless Steel with Stainless Steel pin

FINISHES:

- US3SC, US3, US10, US10B, US26, US26D, US32D

NOTE:

- Available with SecureCoat Lifetime finish. (Specify US3SC when ordering)

PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)	HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (MACHINE)	SCREW SIZE (WOOD)
4 1/2 x 4 1/2	114 x 114	0.180	8	1/2 x 12-24	1 1/4 x 12
5 x 5	127 x 127	0.190	8	1/2 x 12-24	1 1/4 x 12
6 x 4 1/2	152 x 114	0.203	10	1/2 x 1/4-20	1 1/2 x 14
6 x 5	152 x 127	0.203	10	1/2 x 1/4-20	1 1/2 x 14
6 x 6	152 x 152	0.203	10	1/2 x 1/4-20	1 1/2 x 14
5 x 4 1/2	127 x 124	0.190	8	1/2 x 12-24	