

# 1754

## Spring Hinge

**Certifications:**

- BHMA Certified, ANSI 4156.17, Grade 1

**Application:**

- ANSI K51071F  
- Square by 5/8" (16 mm) radius



### PRODUCT SPECIFICATIONS

**MATERIAL:**

- Steel

**FINISHES:**

- USP, 1D, 2D, US3, 3LB, US4, ABA/US5, US10R, US15, AN/US15A, US26, US26D

**PACKAGING:**

- 2 pack with screws

**NOTES:**

- For maximum versatility use all spring hinges or a combination of spring hinges and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges

### PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)		HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT		SCREW SIZE (WOOD)
4 x 4		102 x 102	0.106	8		1 x 9 FH
SERIES	SIZE	RECOMMENDED MAX DOOR WEIGHT (LBS.)	SPRING HINGE	BUTT HINGE	SPRING HINGE LOCATION	
1754	4 x 4	45	1	2	Center	
1754	4 x 4	70	2	1	Top/Btm or Ctr/Btm	
1754	4 x 4	90	3	-	All	