

1764

Spring Hinge

Certifications:

- BHMA Certified, ANSI 4156.17, Grade 1

Application:

- ANSI K51071F
- Square by 5/8" (16 mm) radius



PRODUCT SPECIFICATIONS

MATERIAL:

- Stainless Steel

FINISHES:

- US32, US32D

PACKAGING:

- 2 pack with screws

NOTES:

- For maximum versatility use all spring hinges or a combination of spring hinges and ball bearing hinges. Do not use plain bearing hinges.
- Full spring tension may not be required on all hinges
- Strong wind conditions, drafts, carpeting drag, twisted/misaligned frames, or weatherstripping on doors may require additional spring hinges

PRODUCT SIZE OPTIONS

HINGE SIZE (INCHES)		HINGE SIZE (MM)	GAUGE OF METAL	HOLE COUNT	SCREW SIZE (WOOD)
4 x 4		102 x 102	0.106	8	1 x 9 FH
SERIES	SIZE	RECOMMENDED MAX DOOR WEIGHT (LBS.)	SPRING HINGE	BUTT HINGE	SPRING HINGE LOCATION
1754	4 x 4	45	1	2	Center
1754	4 x 4	70	2	1	Top/Btm or Ctr/Btm
1754	4 x 4	90	3	-	All